



Area Light	ALC7BC27NBWNGN	SafeSite Area Light, 360°, 7000 Lumens, 52 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, Gray, Swivel Bracket, Locking 0-90° - 316 SS, 10' [3 meter] Power Cable, [UL 844 Class I Div. 1]
Area Light	ALC7BC27NNWNGN	SafeSite Area Light, 360°, 7000 Lumens, 52 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, Gray, 10' [3 meter] Power Cable, [UL 844 Class I Div. 1]
Area Light	ALD5BB56NNWNGN	SafeSite Area Light, 360°, 5700 Lumens, 58 Watts, 347 - 480 VAC, Cool White 5000K, Polycarbonate - Diffused, Gray, 10' (3 meter) Power Cable, (UL 844 Class I Div. 2)
Area Light	ALD5BC25NNWNGN	SafeSite Area Light, 360°, 5300 Lumens, 40 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate - Diffused, Gray, 10' [3 meter] Power Cable, [UL 844 Class I Div. 2]
Area Light	ALD5BC26NNWNGN	SafeSite Area Light, 360°, 5300 Lumens, 40 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate - Diffused, Gray, 10' [3 meter] Power Cable, [UL 844 Class I Div. 2]
Area Light	ALD7BC26NNWNGN	SafeSite Area Light, 360°, 5700 Lumens, 40 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, Gray, 10' [3 meter] Power Cable, [UL 844 Class I Div. 2]
Area Light	ALF5BC27NNWNGN	SafeSite Area Light, 360°, 6700 Lumens, 52 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate - Diffused, Gray, 10' [3 meter] Power Cable, [UL 844 Class II Div. 1]

**QUANTITIES SUBJECT TO CHANGE – Please contact your Dialight rep to confirm availability.**

Area Light	ALU5BB56NNWNGN	DuroSite Area Light, 360°, 5700 Lumens, 58 Watts, 347 - 480 VAC, Cool White 5000K, Polycarbonate - Diffused, Gray, 10' (3 meter) Power Cable, (UL 1598/A)
Area Light	ALU5BC25NNWNGN	Vigilant Area Light, 360°, 5300 Lumens, 40 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate - Diffused, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
Area Light	ALU5BC26NNWNGN	Vigilant Area Light, 360°, 5300 Lumens, 40 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate - Diffused, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
Area Light	ALU5BC27NNWNGN	Vigilant Area Light, 360°, 6700 Lumens, 52 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate - Diffused, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
Area Light	HZD5C2N	SafeSite Area Light, 360°, 5300 Lumens, 40 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate - Diffused, 10' [3 meter] Power Cable, Gray, [UL 844 Class I Div. 2]
Area Light	HZFFC2N	SafeSite Area Light - Gen II, 360° Circular , 7250 Lumens, 69 Watts, 100-277V AC, Cool White, Clear Polycarbonate Lens, Anti-Static Coating [CID2, CIID1, CIID2, CIID1, CIID2]
Area Light	HZXCBL2	Accessory - Safety Cable Kit
Area Light	HZXJB075	Accessory- 0.75" Ceiling / Wall / Pole Mount Junction Box
Area Light	HZXJB075PC1	Accessory- 0.75" Ceiling / Wall / Pole Mount Junction Box - with 120VAC Photocell
Area Light	HZXS45	Area Light Stanchion Mount 45° Bracket
Area Light	HZXSAFECBLS	Accessory - Safety Cables - AL - 4'
Area Light	HZXSAFEKIT	Accessory- Safety cable kit
Area Light	HZXSAFETABS	Accessory- Safety Tabs
Area Light	HZXSTAN100S	Accessory- 1.00" (1.315" Pole OD) Slip-Fit Stanchion Mount Junction Box with Junction box mounting hardware (for Area Light products, requires bracket HZXW3 or HZXW7 not included. Brackets not required for Flood Light products)

Area Light	HZXSTAN125S	Accessory- 1.25" (1.660" Pole OD) Slip-Fit Stanchion Mount Junction Box with Junction box mounting hardware (for Area Light products, requires bracket HZXW3 or HZXW7 not included. Brackets not required for Flood Light products)
Area Light	HZXSTAN150S	Accessory- 1.50" (1.900" Pole OD) Slip-Fit Stanchion Mount Junction Box with Junction box mounting hardware (for Area Light products, requires bracket HZXW3 or HZXW7 not included. Brackets not required for Flood Light products)
Area Light	HZXSTAN150T	Accessory- 1.50" (1.900" Pole OD) NPT Threaded Stanchion Mount Junction Box with Junction box mounting hardware (for Area Light products, requires bracket HZXW3 or HZXW7 not included. Brackets not required for Flood Light products)
Area Light	HZXSTAN200S	Accessory- 2.00" (2.375" Pole OD) Slip-Fit Stanchion Mount Junction Box with Junction box mounting hardware (for Area Light products, requires bracket HZXW3 or HZXW7 not included. Brackets not required for Flood Light products)
Area Light	HZXSTAN200T	Accessory- 2.00" (2.375" Pole OD) NPT Threaded Stanchion Mount Junction Box with Junction box mounting hardware (for Area Light products, requires bracket HZXW3 or HZXW7 not included. Brackets not required for Flood Light products)
Area Light	HZXTHAP	Appleton MercMaster III - Retrofit Adapter with retrofit wiring box
Area Light	HZXTHCH	Crouse Hinds Champ - Retrofit Adapter with retrofit wiring box
Area Light	HZXTHGE	GE Filtr-Gard - Retrofit Adapter with retrofit wiring box
Area Light	HZXTHKL	Killark Certilite & Certilite V - Retrofit Adapter with retrofit wiring box
Area Light	HZXTHM2	Appleton MercMaster II - Retrofit Adapter with retrofit wiring box
Area Light	HZXTHP3	Holophane PetroLux II & III - Retrofit Adapter with retrofit wiring box
Area Light	HZXHTB	Thomas and Betts Hazlux - Retrofit Adapter with retrofit wiring box
Area Light	HZXUMA	Accessory - Area Light UMA Hub

Area Light	HZXW3	Accessory- Stainless Steel bracket with mounting hardware
Area Light	HZXW4	Accessory- Stainless Steel bracket with Pipe Clamp and mounting hardware
Area Light	HZXW45	Accessory - Area Light Wall Mount 45° Bracket
Area Light	HZXW7	Accessory- Aluminum bracket with mounting hardware
Area Light	HZXW8	Accessory- Aluminum bracket with Pipe Clamp and mounting hardware



Floodlight	F1D76B2BDENVGN	ProSite F1 Flood, NEMA 6 (Wide 125°), 12,000 Lumens, 81 Watts, 100-277VAC/120-250VDC, Cool White 5000K, Integrated PC Lens + Glass Lens Cover, Angled Bracket, Gray, DALI / 0-10V [UL 844 CID2]
Floodlight	F1D76B2CDENVGN	ProSite F1 Flood, NEMA 6 (Wide 125°), 18,000 Lumens, 124 Watts, 100-277VAC/120-250VDC, Cool White 5000K, Integrated PC Lens + Glass Lens Cover, Angled Bracket, Gray, DALI / 0-10V [UL 844 CID2]
Floodlight	F2E7FL8NDENVGN	ProSite F2 Flood, Asymmetric, 60,000 Lumens, 484 Watts, 120-277VAC/120-250VDC 10kV Surge, Neutral White 4000K, Integrated PC Lens + Glass Lens Cover, Angled Bracket, Gray, Dimming (0-10V) [CE / ENEC / RCM]
Floodlight	F2UN6B8NDENVGN	ProSite F2 Flood, NEMA 6 (Wide 125°), 60,000 Lumens, 484 Watts, 120-277VAC/120-250VDC 10kV Surge, Cool White 5000K, Integrated PC Lens, Angled Bracket, Gray, Dimming (0-10V) [UL 1598/A]
Floodlight	FLD266NC2NG	SafeSite Floodlight 11250 Lumens, 106 Watts, 100-277 VAC, Cool White, NEMA 6, Clear Tempered Glass Lens, [CID2]
Floodlight	FLD466NC4NG	SafeSite Floodlight 15000 Lumens, 135 Watts, 100-277 VAC, Cool White, NEMA 6, Clear Tempered Glass Lens, [CID2]

Floodlight	FLD466NC4NGDR	SafeSite Floodlight 15000 Lumens, 130 Watts, 100-277V, Cool White, NEMA 6, Clear Tempered Glass Lens, Drilling rig accessories kit [CID2]
Floodlight	FLD76B2ANTNNGN	SafeSite Floodlight 11250 Lumens, 106 Watts, 100-277 VAC, Cool White, NEMA 6, Clear Tempered Glass Lens, [CID2]
Floodlight	FLD76B2BNTNNGN	SafeSite Floodlight 15000 Lumens, 135 Watts, 100-277 VAC, Cool White, NEMA 6, Clear Tempered Glass Lens, [CID2]
Floodlight	FLD76B5ANTNNGN	SafeSite Floodlight 11250 Lumens, 112 Watts, 347-480 VAC, Cool White, NEMA 6, Clear Tempered Glass Lens, [CID2]
Floodlight	FLD76B5BNTNNGN	SafeSite Floodlight 15000 Lumens, 135 Watts, 347-480 VAC, Cool White, NEMA 6, Clear Tempered Glass Lens, [CID2]
Floodlight	FLD77B2ANTNNGN	SafeSite Floodlight 11500 Lumens, 106 Watts, 100-277 VAC, Cool White, NEMA 7x6, Clear Tempered Glass Lens, [CID2]
Floodlight	FLD77B2BNTNNGN	SafeSite Floodlight 14750 Lumens, 135 Watts, 100-277 VAC, Cool White, NEMA 7x6, Clear Tempered Glass Lens, [CID2]
Floodlight	FLD77B5ANTNNGN	SafeSite Floodlight 11750 Lumens, 112 Watts, 347-480 VAC, Cool White, NEMA 7x6, Clear Tempered Glass Lens, [CID2]
Floodlight	FLU76B2ANTNNGN	DuroSite Floodlight, NEMA 6, 11,250 Lumens, 106 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, 304 SS Swivel Brkt, Gray, [UL 1598/A]
Floodlight	FLU76B2BNTNNGN	DuroSite Floodlight, NEMA 6, 15,000 Lumens, 135 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, 304 SS Swivel Brkt, Gray, [UL 1598/A]
Floodlight	FLU76B5ANTNNGN	DuroSite Floodlight, NEMA 6, 11,250 Lumens, 112 Watts, 347/480 VAC, Cool White 5000K, Glass - Clear, 304 SS Swivel Brkt, Gray, [UL 1598/A]
Floodlight	FLU76B5BNTNNGN	DuroSite Floodlight, NEMA 6, 15,000 Lumens, 135 Watts, 347/480 VAC, Cool White 5000K, Glass - Clear, 304 SS Swivel Brkt, Gray, [UL 1598/A]
Floodlight	FLU77B2ANTNNGN	DuroSite Floodlight, NEMA 7x6, 11,500 Lumens, 106 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, 304 SS Swivel Brkt, Gray, [UL 1598/A]

Floodlight	FLU77B2BNTNNGN	DuroSite Floodlight, NEMA 7x6, 14,750 Lumens, 135 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, 304 SS Swivel Brkt, Gray, [UL 1598/A]
Floodlight	FLU77B5ANTNNGN	DuroSite Floodlight, NEMA 7x6, 11,750 Lumens, 112 Watts, 347/480 VAC, Cool White 5000K, Glass - Clear, 304 SS Swivel Brkt, Gray, [UL 1598/A]
Floodlight	FLW266NC2NG	DuroSite Floodlight, NEMA 6, 11,250 Lumens, 106 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, 304 SS Swivel Brkt, Gray, [UL 1598/A]
Floodlight	FLW276NC2NG	DuroSite Floodlight 11500 Lumens, 106 Watts, 100-277V AC, Cool White, NEMA 7x6, Clear Tempered Glass Lens,
Floodlight	FLW476NC4NG	DuroSite Floodlight, NEMA 7x6, 14,750 Lumens, 135 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, 304 SS Swivel Brkt, Gray, [UL 1598/A]
Floodlight	FLX1RAB20DB	Right Angle Bracket, 2"
Floodlight	FLX1RAB20LG	RIGHT ANGLE BRKT, 2", GRAY
Floodlight	FLX2LBH20LG	2 Light Bull Horn Brkt, Gray
Floodlight	FLX2RSR20DB	2 Light Round Square Round Bracket
Floodlight	FLX3RPA20DB	Reducer for 3" OD round pole top
Floodlight	FLX3RSR20DB	3 Light Round Square Round Bracket
Floodlight	FLX4LBH20DB	4 Light Bull Horn Bracket
Floodlight	FLX4RBH20DB	4 Light Bull Horn Bracket in Star Configuration
Floodlight	FLX4RPA20DB	Reducer for 4" OD round pole top
Floodlight	FLX4SPA20DB	Internal tenon adapter for 4" square pole top
Floodlight	FLX5SPA20DB	Internal tenon adapter for 5" square pole top
Floodlight	FLX6SPA20DB	Internal tenon adapter for 6" square pole top



High Bay	GAUW24AG	Gateway Controller
High Bay	HBDGCTN	SafeSite High Bay, Circular, 17000 Lumens, 172 Watts, 347-480V AC, Cool White, Clear Tempered Glass Lens, [CID2, CIID2, CIIID1, CIIID2]
High Bay	HBXC1	High Bay Ceiling Mount
High Bay	HBXCAB120K	Accessory - Safety Cables - HOHB - 10' - B-Line
High Bay	HBXCG	High Bay Cable Gland
High Bay	HBXCU	High Bay Ceiling Mount
High Bay	HBXDC	High Bay Dust Cover
High Bay	HBXDC45	High Bay Dust Cover, 45 slope
High Bay	HBXDUALBRCKT	High Bay Dual Bracket
High Bay	HBXGS	High Bay Glare Shield
High Bay	HBXH	High Bay Hook
High Bay	HBXHL	High Bay Hook and Loop
High Bay	HBXLENGC	High Bay Clear Tempered Glass
High Bay	HBXSB	High Bay Safety Bracket Kit 316 SS (4)
High Bay	HBXSBDK	LED Highbay Domed Sand Blast Cover
High Bay	HBXTH347480	High Bay Accessory Top Hat 347/480V
High Bay	HBXTH347480B	High Bay Accessory Top Hat 347/480V
High Bay	HBXW1	High Bay Wall Mount
High Bay	HBXW2	High Bay Swivel Bracket and Cable Gland
High Bay	HBXW3	High Bay Swivel Bracket
High Bay	HBXW3SSL316FT	Forward Throw Stainless steel swivel bracket, 316
High Bay	HBXW3SSL316M	Stainless Steel Swivel High Bay Bracket
High Bay	HEC7MC2CNNWNGN	SafeSite High Bay, Medium, 16000 Lumens, 129 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, Gray, 10' [3 meter] Power Cable, [UL 844 Class I Div. 1]



High Bay	HED7MC2ANNWNGN	SafeSite High Bay, Medium, 11250 Lumens, 80 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, Gray, 10' [3 meter] Power Cable, [UL 844 Class I Div. 2]
High Bay	HED7MC2BNNWNGN	SafeSite High Bay, Medium, 14250 Lumens, 102 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, Gray, 10' [3 meter] Power Cable, [UL 844 Class I Div. 2]
High Bay	HED7MC2CNNWNGN	SafeSite High Bay, Medium, 19500 Lumens, 129 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, Gray, 10' [3 meter] Power Cable, [UL 844 Class I Div. 2]
High Bay	HED7MC2ENNWNGN	SafeSite High Bay, Medium, 26250 Lumens, 186 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, Gray, 10' [3 meter] Power Cable, [UL 844 Class I Div. 2]
High Bay	HEDGMC4KNSNG	SafeSite High Bay, Circular, 18000 Lumens, 144 Watts, 100 - 277 VAC, Cool White, Clear Tempered Glass Lens, [CID2, CIID2]
High Bay	HEGMC4KNSNG	Vigilant High Bay, Medium, 18000 Lumens, 144 Watts, 100 - 277 VAC, Cool White, Clear Tempered Glass Lens, [UL 1598/A]
High Bay	HEU4MC2ANNWNGN	Vigilant High Bay, Medium, 10750 Lumens, 80 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate - Clear, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
High Bay	HEU4MC2BNNWNGN	Vigilant High Bay, Medium, 13750 Lumens, 102 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate - Clear, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
High Bay	HEU4MC2ENNWNGN	Vigilant High Bay, Medium, 25250 Lumens, 186 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate - Clear, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
High Bay	HEU7MC2ANNWNGN	Vigilant High Bay, Medium, 11250 Lumens, 80 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, Gray, 10' [3 meter] Power Cable, [UL 1598/A]

High Bay	HEU7MC2BNNWNGN	Vigilant High Bay, Medium, 14250 Lumens, 102 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
High Bay	HEU7MC2CNNWNGN	Vigilant High Bay, Medium, 19500 Lumens, 129 Watts, 100 - 277 VAC, Cool White 5000K, Glass - Clear, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
High Bay	HEU7MCPCNNWNGN	Vigilant High Bay, Medium, 18000 Lumens, 129 Watts, 480 VAC Passive Driver (Non Dimmable), Cool White 5000K, Glass - Clear, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
High Bay	HEULMC2ANNWNGN	Vigilant High Bay, Medium, 10250 Lumens, 80 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate Dome - Diffused, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
High Bay	HEULMC2BNNWNGN	Vigilant High Bay, Medium, 13250 Lumens, 102 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate Dome - Diffused, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
High Bay	HEULMC2CNNWNGN	Vigilant High Bay, Medium, 18000 Lumens, 129 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate Dome - Diffused, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
High Bay	HLXW3	High Bay 25k Swivel Bracket
High Bay	WOSU12BG2	Occupancy Sensor (narrow angle)
High Bay	WOSU22BG2	Occupancy Sensor (wide angle)
High Bay 60K/45K	H6XCAB72	Accessory - Safety Cables - HOHB - 6' - DROPS
High Bay 60K/45K	H6XH	Vigilant 60K/45K Wet Location Hook
High Bay 60K/45K	H7U7MCDKDNNGN	Vigilant High Output High Bay - Low Profile, Medium, 46,000 Lumens, 308 Watts, 480 VAC Step Down Transformer Driver, Cool White 5000K, Glass - Clear, Gray, Dimming (0-10V), [UL 1598 / UL 1598/A]
Low Bay	LBXLENP	Low Bay Dome Lens

Low Bay	LEDLUC29NNWNGN	SafeSite Low Bay, Ultra Wide, 9000 Lumens, 80 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate Dome - Diffused, Gray, 10' [3 meter] Power Cable, [UL 844 Class I Div. 2]
Low Bay	LEULUC24NNWNGN	Vigilant Low Bay, Ultra Wide, 4000 Lumens, 42 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate Dome - Diffused, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
Low Bay	LEULUC26NNWNGN	Vigilant Low Bay, Ultra Wide, 6000 Lumens, 56 Watts, 100 - 277 VAC, Cool White 5000K, Polycarbonate Dome - Diffused, Gray, 10' [3 meter] Power Cable, [UL 1598/A]
Low Bay	LEULUN29NNWNGN	Vigilant Low Bay, Ultra Wide, 8750 Lumens, 80 Watts, 100 - 277 VAC, Neutral White 4000K, Polycarbonate Dome - Diffused, Gray, 10' [3 meter] Power Cable, [UL 1598/A]



Linear	LPD3C4D2P	SafeSite Linear - Gen II, 3850 Lumens, 29 Watts, 100-277 VAC, Cool White 5000K, Clear Polycarbonate Lens, Low Profile [CID2]
Linear	LPD3C4H2W	SafeSite Linear - Low Profile, 7100 Lumens, 60 Watts, 100-277 VAC, Cool White 5000K, Diffused Polycarbonate Lens [CID2]
Linear	LPD3C4M2P	SafeSite Linear - Gen II, 7900 Lumens, 60 Watts, 100-277 VAC, Cool White 5000K, Clear Polycarbonate Lens, Low Profile, [CID2]
Linear	LPD3C4M2PDR	SafeSite Linear - Gen II, 7000 Lumens, 66 Watts, 100-277V AC, Cool White, Clear Polycarbonate Lens, Low Profile, Drilling rig accessories kit [CID2]
Linear	LPD3C4M2PDRWOB	SafeSite Linear - Gen II, 7000 Lumens, 66 Watts, 100-277V AC, Cool White, Clear Polycarbonate Lens, Low Profile, Drilling Rig, No Bracket [CID2]
Linear	LPM3C4B2W	DuroSite Linear - Low Profile, Medium, 3500 Lumens, 29 Watts, 100-277 VAC, Cool White, Diffused Polycarbonate Lens
Linear	LPM3C4D2P	DuroSite Linear - Low Profile, Medium, 3850 Lumens, 29 Watts, 100-277 VAC, Cool White, Clear Polycarbonate Lens
Linear	LPM3C4H2W	DuroSite Linear - Low Profile, Medium, 7100 Lumens, 60 Watts, 100-277 VAC, Cool White, Diffused Polycarbonate Lens
Linear	LPM3C4M2P	DuroSite Linear - Low Profile, Medium, 7900 Lumens, 60 Watts, 100-277 VAC, Cool White, Clear Polycarbonate Lens
Linear	LPXW4	Mounting bracket. Can be angled at 0, 30, 45, 60 and 90 degrees.
Linear	LSC3C4D3GEX	SafeSite Linear, 3600 Lumens, 34 Watts, 100-277 VAC, Cool White 5000K, Clear Tempered Glass Lens, 2 Feet [CID1]

Linear	LSC3C4M3GEX	SafeSite Linear, 7250 Lumens, 68 Watts, 100-277 VAC, Cool White 5000K, Clear Tempered Glass Lens, 4 feet [CID1]
Linear	LSC3C4M3GEXDR	SafeSite Linear, 7250 Lumens, 78 Watts, 100-277V AC, Cool White, Clear Tempered Glass Lens, 4 feet with drilling rig accessories [CID1]
Linear	LSXENDCAPKIT	Accessory- Chain mount brackets with 2 mounting brackets and hardware
Linear	LSXW5	Accessory- Mounting brackets for 0, 30, 45, 60 or 90 degrees with mounting bracket and mounting hardware, CID
Linear	LTD3C4D2P	SafeSite Linear - Gen II, 3850 Lumens, 29 Watts, 100-277 VAC, Cool White 5000K, Polycarbonate Clear Lens, [CID2]
Linear	LTD3C4M2P	SafeSite Linear - Gen II, 7900 Lumens, 60 Watts, 100-277 VAC, Cool White 5000K, Polycarbonate Clear Lens, [CID2]
Linear	LTD3C4M2PDR	SafeSite Linear - Gen II, 7000 Lumens, 66 Watts, 100-277V AC, Cool White, Polycarbonate Clear Lens, Drilling rig accessories kit [CID2]
Linear	LTM3C4D2P	DuroSite Linear - Top Conduit, Medium, 3850 Lumens, 29 Watts, 100-277 VAC, Cool White, Clear Polycarbonate Lens
Linear	LTM3C4H2W	DuroSite Linear - Top Conduit, Medium, 7100 Lumens, 60 Watts, 100-277 VAC, Cool White, Diffused Polycarbonate Lens
Linear	LTM3C4M2P	DuroSite Linear - Top Conduit, Medium, 7900 Lumens, 60 Watts, 100-277 VAC, Cool White, Clear Polycarbonate Lens
Linear	LTX8FTENDCAP	End to end linear mounting kit
Linear	LTXENDCAPKIT	Accessory- Chain mount brackets with 2 mounting brackets and hardware
Linear	LTXLENPD	Accessory - Clear Poly Replacement lens
Linear	LTXSAFEKIT	Accessory - LIN II END CAP SAFETY CABLES
Linear	LTXW4	Accessory- Mounting brackets for 0, 30, 45, 60 or 90 degrees with mounting bracket and mounting hardware
Linear	LTXW4LP	Accessory - Mounting Bracket, 0 or 15 degrees, Low Profile